

Site Event Buffer - Feature Specification Comparison

Feature	Description	NET-PATH	NET-PATHm
Communication Ports	RS232, RJ45	4 or 8 ports	2 ports
Network	10/100Base-T	10/100Base-T	10/100Base-T
Contact Sensors	Hard contact sensors	8 or 16 sensors	4 sensors
Modem	56Kbps, Class 2 fax	1 internal modem	1 internal modem
Memory	Program & data storage	32 Mb Flash 128 Mb SDRAM	16 Mb Flash 64 Mb SDRAM
Segment Manager(option)	SNMP elements managed	10 or 20	5
Output Controls	Controlled output devices	2 SPDT relays 200 ma	None
Integrated Analog Sensors	Analog sensors for reporting temperature and voltage	1 temperature (50-110F) 1 DC voltage (0-60VDC)	None
System Power	Universal power supply DC power supply	110/220 VAC 48 VDC	110/220 VAC 48 VDC
Battery Backup	Integrated UPS: maintains full function up to 2 hours	Yes	Yes
RTC Sleep Battery	Provides long-term backup for real time clock	Yes	Yes
Diagnostics	LCD display for system information & diagnostics	Yes	No
Watchdog	Watchdog timer	Yes	Yes
Mounting Configuration	19" rack and desktop	Both	Desktop
Dimensions	Height Width Depth	1.75 " (IU) 18.0" 10.5"	1.82 " 9.75" 11.0"
Operating Enviroment	Temperature - operating: 50 - 110 degrees F Non - operating: 20 - 140 degrees F Relative humidity, noncondensing: 20% - 80%		



Specifications subject to change without notice.
© 2005 Teltronics Incorporated.